

UREAPRIM CONCRETE epoxy primer for concrete surfaces.

## DESCRIPTION

Epoxy primer for preparing concrete surfaces before applying polyurea UREASPRAY.

## ADVANTAGES

Easy to apply, seals the concrete surface and increases the polyurea adhesion.

## APPLICATION PRESCRIPTIONS

- Mix A and B component thoroughly.
- Apply to clean, dry and correctly repaired concrete with a roller.
- Wait at least 2-6 hours before spraying the UREASPRAY, depending on the temperature.

## TECHNICAL DATA

<b>Volatile Organic Compounds - VOC (g/l)</b>	Compliant with European environmental legislation
<b>Max. humidity of concrete during application</b>	5%
<b>Recoating window depending on temperature</b>	min. 3-6 h, max. 24-48 h
<b>Adhesion to dry concrete (MPa)</b>	> 5.2 (fracture in concrete)
<b>Adhesion to wet concrete (MPa)</b>	> 2.39 (NBN EN 1542) (fracture in concrete)

## USAGE

± 250 g/m<sup>2</sup> depending on the porosity of the surface.

## PACKAGING

10 kg per set (6 kg A component, 4 kg B component)

## STORAGE

12 months in original packaging. Keep original drums tightly closed to prevent contamination by humidity. Store in clean and dry place between 10°C and 30°C.

## SAFETY AND HEALTH PRECAUTIONS

For more information, consult the safety data sheet.